

GOLF CART/UTILITY VEHICLE - DOT Approved For Highway Use

POWER KING TOURISTER

- *Designed For Golf Carts And Electric Vehicles*
- *Multi-Purpose Tread Design*
- *Wide-Flotation Size*
- *DOT Approved For Highway Use*



ARTICLE NO.	TIRE SIZE	LR/PR	TREAD DEPTH (INCH)	TYPE	RIM WIDTH (INCH)	OUTSIDE DIAMETER (INCH)	SECTION WIDTH (INCH)	SLR	REVS PER MILE	WGT	MAX. LOAD @ PSI 10 MPH
PKT12	205/50-10	B/4	10/32	TL	6.50	17.7	7.8	8.3	1172	13.2	665 @ 30

GOLF CART - RIB

STRAIGHT RIB

- *Straight Rib Design For Minimal Turf Damage*
- *Wide Tread Face For Traction, Reduced Turf Disturbance And Weight Disbursement*



ARTICLE NO.	TIRE SIZE	LR/PR	TREAD DEPTH (INCH)	TYPE	RIM WIDTH (INCH)	OUTSIDE DIAMETER (INCH)	SECTION WIDTH (INCH)	SLR	REVS PER MILE	WGT	MAX. LOAD @ PSI 10 MPH
LRW35	18X8.50-8	B/4	6/32	TL	7.00	17.5	8.5	7.76	1189	10	815 @ 22

GOLF CART

TURF RIB

- *Multi-Purpose Turf Friendly Design*
- *Designed For Maximum Traction, Reduced Turf Disturbance And Weight Disbursement*



ARTICLE NO.	TIRE SIZE	LR/PR	TREAD DEPTH (INCH)	TYPE	RIM WIDTH (INCH)	OUTSIDE DIAMETER (INCH)	SECTION WIDTH (INCH)	SLR	REVS PER MILE	WGT	MAX. LOAD @ PSI 10 MPH
WDG50	18X8.50-8	B/4	6/32	TL	7.00	17.7	8.4	8.00	-	4	815 @ 22

GOLF CART - SAWTOOTH

SAWTOOTH RIB

- *Multi-Purpose Turf Friendly Design*
- *Square Shoulder Design For Maximum Traction, And Weight Disbursement*



ARTICLE NO.	TIRE SIZE	LR/PR	TREAD DEPTH (INCH)	TYPE	RIM WIDTH (INCH)	OUTSIDE DIAMETER (INCH)	SECTION WIDTH (INCH)	SLR	REVS PER MILE	WGT	MAX. LOAD @ PSI 10 MPH
SST50	18X8.50-8	B/4	7/32	TL	7.00	17.7	8.4	7.76	1175	12	815 @ 22

LAWN AND GARDEN

TURF



- **Multi-Purpose Turf Friendly Design For Utility Vehicles Or Golf Carts**
- **Square Shoulder Design For Maximum Traction And Weight Disbursement**

ARTICLE NO.	TIRE SIZE	LR/PR	TREAD DEPTH (INCH)	TYPE	RIM WIDTH (INCH)	OUTSIDE DIAMETER (INCH)	SECTION WIDTH (INCH)	SLR	REVS PER MILE	WGT	MAX. LOAD @ PSI 10 MPH
LWW05	410/350-4	B/4	3/32	TL	3.25	10.7	3.9	–	–	2	350 @ 50
LWW07	11X4.00-4	B/4	3/32	TL	3.25	10.7	4.1	–	–	3	330 @ 46
LWW10	11X4.00-5	B/4	5/32	TL	3.00	11.3	4.1	4.97	1841	3	325 @ 46
LWW20	13X5.00-6	B/4	5/32	TL	3.50	13.2	4.9	5.81	1576	4	460 @ 40
LWW23	13X6.50-6	B/4	6/32	TL	5.38	13.0	6.3	5.72	1600	4	460 @ 22
LWW25	15X6.00-6	B/4	6/32	TL	4.50	14.6	6.3	6.38	1425	6	570 @ 30
LWW17	480/400-8	B/4	4/32	TL	3.75	16.6	4.7	–	–	5	670 @ 42
LWW30	16X6.50-8	B/4	6/32	TL	5.38	16.2	6.5	7.28	1284	8	620 @ 28
LWW34	16X7.50-8	B/4	9/32	TL	5.38	16.3	7.2	–	–	8	680 @ 24
LWW36	18X6.50-8	B/4	4/32	TL	5.00	17.9	6.5	–	–	8	770 @ 28
LWW38	18X7.00-8	B/4	9/32	TL	5.38	13.8	7.0	–	–	3	785 @ 26
LWW40	18X8.50-8	B/4	8/32	TL	7.00	17.7	8.4	7.76	1175	10	815 @ 22
LWW45	18X9.50-8	B/4	8/32	TL	7.00	18.2	9.3	7.87	1143	10	1040 @ 22
FTW50	20X8-8	A/2	6/32	TL	5.38	19.1	7.6	8.35	1089	8	560 @ 12
FTW41	20X10-8	B/4	7/32	TL	7.00	19.5	9.1	8.66	1067	12	1130 @ 22
LWW46	18X10.50-10	B/4	11/32	TL	8.50	19.1	9.8	–	–	12	990 @ 20
FTW54	20X8-10	B/4	9/32	TL	6.00	19.8	8.1	–	–	12	895 @ 24
FTW56	20X10-10	B/4	10/32	TL	8.00	19.9	9.6	–	–	13	1160 @ 22
FTW55	23X8.50-12	B/4	7/32	TL	7.00	23.0	8.1	9.72	904	14	1115 @ 22
FTW57	23X9.50-12	B/4	7/32	TL	7.00	22.8	8.9	10.03	912	15	1380 @ 22
FTW40	23X10.50-12	B/4	7/32	TL	7.00	23.0	8.1	9.72	904	14	1115 @ 22
FTW58	26X12-12	B/4	7/32	TL	7.00	22.8	8.9	10.03	912	15	1380 @ 22

LAWN AND GARDEN

STRAIGHT RIB



- **Straight Rib Design For Minimal Turf Damage**
- **For Use On Utility Vehicles And Golf Carts**
- **Square Shoulder Design For Maximum Traction And Weight Disbursement**

ARTICLE NO.	TIRE SIZE	LR/PR	TREAD DEPTH (INCH)	TYPE	RIM WIDTH (INCH)	OUTSIDE DIAMETER (INCH)	SECTION WIDTH (INCH)	SLR	REVS PER MILE	WGT	MAX. LOAD @ PSI 10 MPH
LRW10	11X4.00-5	B/4	4/32	TL	3.00	11.0	3.9	–	–	3	325 @ 46
LRW20	13X5.00-6	B/4	4/32	TL	3.50	12.9	3.5	5.75	1612	3	440 @ 40
LRW23	13X6.50-6	B/4	3/32	TL	4.50	13.2	6.4	5.91	1576	5	460 @ 28
LRW25	15X6.00-6	B/4	5/32	TL	4.50	14.2	6.1	6.38	1465	5	570 @ 30
LRW30	16X6.50-8	B/4	6/32	TL	5.38	16.2	6.7	7.28	1284	7	620 @ 28
LRW35	18X8.50-8	B/4	6/32	TL	7.00	17.5	8.5	7.76	1189	10	815 @ 22
LRW36	18X9.50-8	B/4	5/32	TL	7.00	18.5	8.5	8.19	1124	9	1040 @ 40

COMMERCIAL MEDIUM TRUCK
 LOW PLATFORM BIAS TRAILER
 SPECIALTY TRAILER TIRES
 LIGHT TRUCK
 AGRICULTURAL & SKID STEER
 AGRICULTURAL - GOLF CART, LAWN & GARDEN
 ALL TERRAIN VEHICLE
 INDUSTRIAL SPECIALTY TIRES
 OFF THE ROAD
 STEEL TRUCK WHEELS
 FLAPS
 VALVE STEMS

LAWN AND GARDEN

SAWTOOTH RIB

- *Square Shoulder Design For Maximum Traction And Weight Disbursement*



ARTICLE NO.	TIRE SIZE	LR/PR	TREAD DEPTH (INCH)	TYPE	RIM WIDTH (INCH)	OUTSIDE DIAMETER (INCH)	SECTION WIDTH (INCH)	SLR	REVS PER MILE	WGT	MAX. LOAD @ PSI TO MPH
SSW02	2.80/2.50-4 NHS	B/4	3/32	TL	2.25	9.0	2.9	—	—	2	295 @ 50
SSW05	4.10/3.50-4 NHS	B/4	5/32	TL	2.50	10.7	3.7	4.57	1944	2	350 @ 50
SSW10	4.10/3.50-5 NHS	B/4	5/32	TL	3.00	11.7	3.8	5.16	1778	2	380 @ 50
SSW15	4.10/3.50-6 NHS	B/4	4/32	TL	2.50	12.8	3.8	5.63	1625	3	445 @ 40
SSW20	5.30/4.50-6 NHS	B/4	6/32	TL	4.25	14.7	5.3	6.38	1415	4	660 @ 65

LAWN AND GARDEN

STUD

- *Stud Design For Long Wearing Traction*
- *Square Shoulder Design For Maximum Traction And Weight Disbursement*



ARTICLE NO.	TIRE SIZE	LR/PR	TREAD DEPTH (INCH)	TYPE	RIM WIDTH (INCH)	OUTSIDE DIAMETER (INCH)	SECTION WIDTH (INCH)	SLR	REVS PER MILE	WGT	MAX. LOAD @ PSI TO MPH
SUW05	4.10/3.50-4 NHS	B/4	5/32	TL	2.50	10.7	3.7	4.57	1944	2	350 @ 50
SUW10	4.10/3.50-5 NHS	B/4	6/32	TL	3.25	11.6	3.9	5.16	1793	2	380 @ 50
SUW15	4.10/3.50-6 NHS	B/4	7/32	TL	3.25	12.6	3.8	5.63	1651	3	445 @ 50
SUW20	4.80/4.00-8 NHS	B/4	6/32	TL	3.75	16.5	4.7	7.40	1261	4	670 @ 42

LAWN AND GARDEN

WHEELBARROW RIB

- *Wheelbarrow Rib Design For Smooth, Easy Control*
- *Round Shoulder Design For Less Rolling Resistance*



ARTICLE NO.	TIRE SIZE	LR/PR	TREAD DEPTH (INCH)	TYPE	RIM WIDTH (INCH)	OUTSIDE DIAMETER (INCH)	SECTION WIDTH (INCH)	SLR	REVS PER MILE	WGT	MAX. LOAD @ PSI
WWW08	4.00-6	A/2	3/32	TL	2.50	10.5	4.8	4.62	1981	2	390 @ 30
WWW11	4.00-8	B/4	3/32	TL	2.50	16.0	4.6	7.04	1300	3	670 @ 40